

CERTIFICATE OF PHYSICAL PROPERTIES Of thickness 20.0mm

KalsiDeck® is a wood replacement product designed for interior and exterior decking and staircase application. The decking boards are available with a Meranti texture in monolithic and longitudinal V-Line in the middle of the board.

Benefits

- Resistant to the attack of termites, insects and most other vermin
- Moist, mould and water resistant
- Wide variety of thickness and applications
- Impact resistant
- Dimensionally stable
- Easy to work and install

General Technical Properties	Value	Standard
Dimensional Conformity - Thickness - Length - Width - Straightness of edges - Squareness of edges	Level II (Pass)	ISO 8336:2009
Density	≥ 1300 kg/m ³	ISO 8336:2009
Moisture content	≤ 15%	ASTM C1185
Water absorption	≤ 33%	ASTM C1185
Moisture movement	≤ 0.04 %	ISO 8336:2009
Thermal conductivity	0.27 W/mK	ISO 8336:2009
Modulus of rupture (Category A)	≥ 7MPa (Class 2)	ISO 8336:2009

Durability		
Heat-Rain performance	Pass	ISO 8336:2009
Warm water performance	Pass	ISO 8336:2009
Freeze-thaw performance	Pass	ISO 8336:2009
Soak-dry performance	Pass	ISO 8336:2009

Reaction to Fire		
Non-combustibility	Non-combustible	BS 476 Part 4: 1970
Surface spread of flame	Class 1	BS 476 Part 7:1997
Fire propagation index	l = 1.6 i(1) = 1.0 i(2) = 0.3 i(3) = 0.3	BS 476 Part 6:1989

Eternit

Unit 19-02-01, Level 2, Wisma Tune,
No. 19, Lorong Dungun, Damansara Heights,
50490 Kuala Lumpur, Malaysia.
Tel: +60 (3) 2095 5111
Fax: +60 (3) 2095 6111
Email: info@eternit-ap.com