

CERTIFICATE OF PHYSICAL PROPERTIES

Of thickness 15.0mm, 18.0mm, 20.0mm

KalsiFloor® is a strong fibre cement panel suitable for internal flooring applications. can be directly finished (with carpet or vinyl tiles) in residential projects or offices, or with reinforced mortar screed in industrial and heavy duty applications. KalsiFloor® is a superb alternative to concrete slabs because it is an incredible lightweight solution. KalsiFloor® is fast and clean to install.

Benefits

- Resistant to the attack of termites, insects and most other vermin
- Moist, mould and water resistant
- Wide variety of thickness and applications
- Impact resistant
- Dimensionally stable
- Easy to work and install

General Technical Properties	Value	Standard
Dimensional Conformity - Thickness - Length - Width - Straightness of edges - Squareness of edges	Level II (Pass)	ISO 8336:2009
Density	≥ 1300 kg/m ³	ISO 8336:2009
Moisture content	≤ 15%	ASTM C1185
Water absorption	≤ 33%	ASTM C1185
Moisture movement	≤ 0.04 %	ISO 8336:2009
Thermal conductivity	0.27 W/mK	ISO 8336:2009
Modulus of rupture (Category C)	≥ 10MPa (Class 3)	ISO 8336:2009

Durability		
Warm water performance	Pass	ISO 8336:2009
Soak-dry performance	Pass	ISO 8336:2009

Reaction to Fire		
Non-combustibility	Non-combustible	BS 476 Part 4: 1970
Surface spread of flame	Class 1	BS 476 Part 7:1997
Fire propagation index	l = 1.6 i(1) = 1.0 i(2) = 0.3 i(3) = 0.3	BS 476 Part 6:1989

Eternit

Unit 19-02-01, Level 2, Wisma Tune,
No. 19, Lorong Dungun, Damansara Heights,
50490 Kuala Lumpur, Malaysia.
Tel: +60 (3) 2095 5111
Fax: +60 (3) 2095 6111
Email: info@eternit-ap.com